

# FHQ-C / RZQG

Features	Benefits
Designed for Seasonal Efficiency	Performs in all seasonal conditions, Improving energy efficiencies and offering lower running costs
Maximum ceiling height of up to 4.3m	Can be used to provide efficient heating and cooling in rooms with high ceilings
EDP Setting	Configures system for continuous cooling and humidity control, creating optimum conditions for IT equipment rooms
D3 connection as standard	Allows integration of split system into Daikin building management systems
Selectable evaporating and condensing temperatures	Improves energy efficiency of the 'out of the box' system by 20%, saving money on running costs

Indoor unit			Single Phase				3 Phase				
			FHQ71C	FHQ100C	FHQ125C	FHQ140C	FHQ71C	FHQ100C	FHQ125C	FHQ140C	
Cooling Capacity	Nominal	kW	6.8	9.5	12	13.4	6.8	9.5	12	13.4	
	UK Total	kW	7.76	10.8	13.6	14.9	7.76	10.8	13.6	14.9	
	UK Sensible	kW	5.32	7.44	9.3	10.25	5.32	7.44	9.3	10.25	
Heating Capacity	Nominal	kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A++		A+		A++		A+		
		Pdesign	kW	6.80	9.50	12.00	-	6.80	9.50	12.00	-
		SEER		6.95	6.11	6.01	-	6.95	6.11	6.01	-
	Heating (Average climate)	Annual energy consumption	kWh	342	544	698	-	342	544	698	-
		Energy label		A+	A++	A+	-	A+	A++	A+	-
		Pdesign	kW	7.60	11.30	14.13	-	7.60	11.30	14.13	-
		SCOP		4.32	4.61	4.23	-	4.32	4.61	4.23	-
Annual energy consumption	kWh	2,462	3,431	4,676	-	2,462	3,431	4,676	-		
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER		3.82	4.13	3.52	3.31	3.82	4.13	3.52	3.31	
	COP		4.13	4.42	3.89	3.63	4.13	4.42	3.89	3.63	
	Annual energy consumption	kWh	890	1,245	1,790	2,025	890	1,245	1,790	2,025	
Nominal Power Input	Cooling / Heating	kW	1.78 / 1.82	2.49 / 2.6	3.58 / 3.48	4.27 / 4.27	1.78 / 1.82	2.49 / 2.6	3.58 / 3.48	4.05 / 4.27	
Dimensions	Height x Width x Depth	mm	235 x 1270 x 690	235 x 1590 x 690			235 x 1270 x 690	235 x 1590 x 690			
Weight		kg	32	38			32	38			
Air Flow Rate	High / Low	m³/min	20.5 / 14	28 / 20	31 / 23	34 / 24	20.5 / 14	28 / 20	31 / 23	34 / 24	
Sound Power	High	dBA	64	66	67	69	64	66	67	69	
Sound Pressure	High / Low	dBA	38 / 34	42 / 34	44 / 37	46 / 38	38 / 34	42 / 34	44 / 37	46 / 38	
Refrigerant		Type	R410A				R410A				
Power Supply			From outdoor unit				From outdoor unit				
Controller			BRC1E52A wired				BRC1E52A wired				

Outdoor unit			RZQG71L9V1	RZQG100L9V1	RZQG125L9V1	RZQG140L9V1	RZQG71L8Y1	RZQG100L8Y1	RZQG125L8Y1	RZQG140LY1
Dimensions	Height x Width x Depth	mm	990 x 940 x 320	1430 x 940 x 320			990 x 940 x 320	1430 x 940 x 320		
Weight		kg	78	102			80	101		
Operation Range	Cooling Min~Max	°CDB	-15°C to +50°C				-15°C to +50°C			
	Heating Min~Max	°CWB	-20°C to +15.5°C				-20°C to +15.5°C			
Sound Power	High	dBA	64	66	67	69	64	66	67	69
Sound Pressure	Nom.	dBA	48	50	51	52	48	50	51	52
Refrigerant		Type	R410A				R410A			
Power Supply			1~ / 50Hz / 220 - 240v				3~ / 50Hz / 400v			
Piping Connections	Liquid (OD)/Gas	inches	3/8 / 5/8				3/8 / 5/8			
Piping Length (Maximum)		m	50	75			50	75		
Max Installation Height Difference		m	30				30			

## Accessories

- Duty rotation controller (RTD10)
- Wireless remote controller (BRC7E63)
- Fresh Air intake kit (KDDQ50A140)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)